

MODEL: UP 750W Series



FEATURE

- * EASY, OPERATION , WITH JOG-DIAL
- * 3 1/2 DIGITAL AUTO REANGE V,A METER
- * CC/CV/OVP INDICATOR
- * OVER LOAD & TEMPERATURE PROTECTED
- * CONSTANT VOLTAGE & CURRENT OUTPUT
- * V-SENSE CONNECT
- * OVER LOAD PROTECTION
- * HIGH ACCURACY & HIGH STABILITY
- * LOW RIPPLE AND LOW NOISE
- * REMOTE CONTROL FUNCTION

SPEC

SPECIFICATION UP SERIES 750W	MODEL	UP-3002	UP-3020	UP-6010
	OUTPUT	300V 2A	30V 20A	60V 10A
OUTPUT VOLTAGE(CV)		0~150V	0~300V	0~30V
OUTPUT CURRENT(CC)		0~5A	0~2A	0~10A
RIPPLE REJECTION (rms/p-p)		6/60 mV	4/40 mV	3/30 mV
LINE REGULATION		30 mV	30 mV	30 mV
LOAD REGULATION		50 mV	40 mV	40 mV
VOLTAGE RESOLUTION		0.1V → 1V	0.1V → 1V	0.01V → 0.1V
CURRENT RESOLUTION		0.001A → 0.01A	0.001A → 0.01A	0.01A → 0.1A
TRANSIENT RECOVERY TIME		100 μ s (50%LOAD CHARGE,MINIMUM LOAD 0.5A)		
DISPLAYER	VOLTAGE	3 1/2 DIGITAL AUTO RANGE DIGITAL DISPLAY		
	CURRENT	3 1/2 DIGITAL AUTO RANGE DIGITAL DISPLAY		
PROTECTION	OVER VOLTAGE	FULL SCALE OF DC OUTPUT VOLTAGE + 9%		
	OVER CURRENT	FULL SCALE OF DC OUTPUT CURRENT + 9%		
	TEMPERATURE	ONLY HEAT SINK 85 $^{\circ}$ C		
OPERATING ENVIRONMENT		0~50 $^{\circ}$ C ,80%R.H.		
AC POWER SOURCE		AC 110/220V \pm 10% , 50/60 Hz (CUSTOMER MADE)		
ANALOG INPUT FOR VOLTAGE CONTROL		0~10V DC INPUT / 0~FULL SACLE DC OUTPUT VOLTAGE		
V-SENSE		FOR LOAD REGULATION VOLTAGE DROP		
ACCESSORIES		INPUT POWER CORD, MANUAL , OUTPUT CABLE		
Weight(Approx)		42 kg	42 kg	44 kg
DIMENSION(W*H*D mm)		420*200*450	420*200*450	420*200*450