

TM-16E

600A Autoranging AC Clamp-On Meter

- 3½ digits LCD with maximum reading 2000.
- Overload indication: "1".
- Low battery indication: "BAT".

FUNCTIONS

- Function keys: Data Hold(TM-16E/TM-23E) Select Range(TM-16E).
- Test ranges: ACV, ACA, DCV (TM-16E), Ω, Continuity (TM-16E/TM-23E) Diode (TM-16E).



TM-23E



Specifications

| Model | TM-16E | TM-23E |
|-----------------------|----------------------------|---------------------|
| Max measuring current | 600A | 600A |
| Display counts | 2000 | 2000 |
| Max conductor size | 30mm | 35mm |
| AC Current | 0.1A~600A (Auto) ±(2.0%+5) | 0.1A~600A ±(2.0%+5) |
| AC Voltage | 0.1~600V ±(1.5%+5) | 0.1~600V ±(1.5%+5) |
| DC Voltage | 0.1V~600V ±(1.0%+2) | — |
| Resistance | 0.1~200Ω ±(0.8%+3) | 0.1~200Ω ±(0.8%+3) |
| Continuity buzzer | YES | YES |
| Diode | Test Volt 1.6VDC | — |
| Autorange | YES | YES |
| Auto power OFF | YES | — |
| Peak hold | — | — |
| Data hold | YES | YES |
| ACA(auto) | 0.1A~400A | 0.1A~400A |
| SIZE(L*W*H) | 195*64*30 | 218*75*43 |
| WEIGHT | 240 | 335 |